EIPEL et al., Ser. No. 09/214,868

IN THE CLAIMS

Please amend the claims as follows.

- 1-12. (canceled)
- 13. (currently amended) A solid support for analytical measurement methods which comprises an inert solid support material on which hydrophilic measurement zones are each surrounded by a hydrophobic zone and wherein <u>a</u> hydrophilic discontinuities area separate separates the hydrophobic zones from one another, and where the number of measurement points applied per cm² of the support is greater than or equal to 10.
- 14. (previously presented) A sollid support as claimed in claim 13, wherein the hydrophilic measurement zones applied to the substrate are separated from one another by non-continuous hydrophobic zones in the forms of rings.
- 15. (currently amended) A support as claimed in claim 13, wherein the support material used is glass, ceramic, quartz, metal, stone, plastic, rubber silicon or porcelain.
- 16. (currently amended) A support as claimed in claim 13, wherein a transparent support material selected from the group consisting of glass, quartz, silicon or plastic is used.
- 17. (previously presented) An analytical measurement method which comprises applying liquid analysis samples in the hydrophilic measurement zones of a support as claimed in claim 13, overlaying the hydrophilic measurement zones with a hydrophobic liquid and performing the analysis.

EIPEL et al., Ser. No. 09/214,868

- 18. (previously presented) An analytical measurement method as claimed in claim 17, wherein the analytical measurement is carried out in an atmosphere which is virtually saturated with water vapor.
- 19. (previously presented) The analytical measurement method of claim 17, wherein the analytical measurement is carried out while cooling the support.
- 20. (previously presented) The analytical measurement method of claim 17 adapted for diagnostic methods, screening of active substances, combinatorial chemistry, crop protection, toxicology or environmental protection.
- 21. (previously presented) A sollid support as claimed in claim 13, wherein additional surface loading is applied to the hydrophilic measurement zones.